



serTEMCAR



GOLF ARABALARI

GOLF CARS



SerTEM CAR

15 YILLIK TECRÜBE 15 YEARS OF EXPERIENCE

Golf Arabaları, Elektrik , Elektronik ve Dizel Forklift ve İstif Araçları-
da tecrübeli ekip ve ekipmanla siz değerli müşterilerimizin servis
taleplerini beklemekteyiz.

*We are waiting for the service requests of our valued customers with our
experienced team and equipment in Golf Carts, Electric, Electronic and
Diesel Forklifts and Trucks.*



Elektrikli golf araçlarının tüm markalarına ve modellerine servis, bakım onarım, tamir, arıza tesbit ve giderilmesi konusunda hizmet vermekteyiz.

We provide service, maintenance, repair, repair, troubleshooting and troubleshooting for all brands and models of electric golf vehicles.

Konusunda eğitimli ve deneyimli ekibimiz, teknolojiyi yakından takip eden servis alt yapımız, yerli ve yabancı Elektrikli Araç üretici ile yaptığımız çözüm ortaklıkları ile siz değerli müşterilerimize garantili ve kaliteli bakım, onarım ve servis hizmetleri sunmaktayız.

Firmamız; Hem çevrimiçi hem de çevrimdışı birçok yedek parça tedarikçisi ile sorunlarınıza kısa zamanda çözüm üretmekte ve araçlarınızın güvenle kullanılmasını sağlamaktadır.

Golf arabalarınızın performansını korumak ve aynı zamanda dayanıklılığını sağlamak için düzenli olarak bakım yapmanız gerekmektedir.

With our trained and experienced team, our service infrastructure that closely follows the technology, and our solution partnerships with domestic and foreign Electric Vehicle manufacturers, we offer guaranteed and quality maintenance, repair and service to our valued customers.

Our company; With many spare parts suppliers both online and offline, it provides solutions to your problems in a short time and ensures that your vehicles can be used safely.

To maintain the performance of your golf carts and at the same time ensure their durability, you need to perform regular maintenance.

BAKIM İPUÇLARI - CARE TIPS

AKÜ BAKIMI BATTERY MAINTENANCE

Akü, elektrikli Elektrikli Araçların hayati bir parçasıdır ve uygun şekilde korunmazsa çok maliyetli olabilir. Düzgün bir bakımlı batarya 4-5 yıl dayanmalıdır.

Yalnızca büyük Elektrikli Araç üreticileri tarafından kullanılan en kaliteli pilleri kullanıyoruz.

The battery is a vital part of electric Electric Vehicles and can be very costly if not properly maintained. A properly maintained battery should last 4-5 years. We only use the highest quality batteries used by the major Electric Vehicle manufacturers.

LASTİK BAKIMI TIRE MAINTENANCE

Lastik basıncını aylık olarak kontrol edin ve üreticinin tavsiye ettiği basıncı doldurun (çoğu lastik için 22 psi). Şişirilmiş bir lastik, dengesiz aşınmaya neden olabilir ve lastiğin ömrünü kısaltabilir ve ayrıca araba performansını da zorlayabilir.

Check the tire pressure monthly and top up the manufacturer's recommended pressure (22 psi for most tires). An inflated tire can cause uneven wear and shorten the life of the tire, as well as strain car performance.

FREN BAKIMI BRAKE MAINTENANCE

Elektrikli araçların mekanik frenler her 12 ayda bir kontrol edilmeli ve servisi yapılmalıdır. Bu, pedlerin, tamburların, kabloların ve pedalın kontrol edilmesini, temizlenmesini ve ayarlanmasını içerir. Uygun şekilde bakım yapılmayan frenler pahalı onarımlara neden olabilir ve ayrıca arabadaki yolcular için tehlike oluşturabilir.

Mechanical brakes of electric vehicles should be checked and serviced every 12 months. This includes checking, cleaning and adjusting the pads, drums, cables and pedal. Improperly maintained brakes can result in expensive repairs and also pose a hazard to occupants in the car.

YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

4 Kişilik Yardımcı Golf Arabası Z2C mavi

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkışı 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28kmh
Menzil (yükü) şuna göre: 20km/s hızla düz yol	28kmh
Minimum dönüş yarıçapı	25m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	530kgsv
boyutlar	
Genel boyutlar: LxWxH (mm)	2370x1210x1950mm
ön/arka tekerlek mesafesi (mm)	front:880mm/rear:998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi. Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stili dönüş işığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	On mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



4 Person Utility Golf Cart Z2C blue

PASSENGER TRANSPORT VEHICLES

For Golf Course

Ürün Bilgisi

2 Seats Utility Golf Cart	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge, Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28km/h
Range (loaded) based on flat road at a speed of 20km/h	28km/h
Minimum turning radius	25m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgs
Dimensions	
Overall dimensions: L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm / rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations ('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle/leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

2 Kişilik Golf Arabası

Z2 simli

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj girişi voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28kmh
Menzil (yükü) şuna göre: 20km/s hızla düz yol	28kmh
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Araabanın ağırlığı (pillerle birlikte)	530kgsv
boyutlar	
Genel boyutlar: LWH (mm)	2370*1210*1950mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Çövede ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması. Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlenebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstül dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Caz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



2 Person Golf Cart Z2 silvery

PASSENGER TRANSPORT VEHICLES

For Golf Course

Product information

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge. Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgsv
Dimensions	
Overall dimensions: LWH (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO/SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

2 Kişilik Golf Arabası

Z2 mavi

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28km/h
Menzil (yükü) şuna göre: 20km/h hızla düz yol	28km/h
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	530kgsv
boyutlar	
Genel boyutlar: LxVxH (mm)	2370x1210x1950mm
ön/arka tekerlek mesafesi (mm)	front:880mm/rear:998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlenebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	iki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stil dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli (1.22m x 0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



2 Person Golf Cart Z2 Blue

PASSENGER TRANSPORT VEHICLES

For Golf Course

Product information

2 Seats Utility Golf Cart	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	25m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight(with batteries)	530kgsv
Dimensions	
Overall dimensions L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO/SOC, Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği. Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28kmh
Menzil (yükli) şuna göre: 20km/s hızla düz yol	28kmh
Minimum dönüş yarıçapı	25m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	530kgs
boyutlar	
Genel boyutlar: LWH (mm)	2370*1210*1950mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

2 Kişilik Golf Arabası Z2 Kırmızı

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması. Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlenebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstül dönüş işığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



2 Person Golf Cart Z2 Red

PASSENGER TRANSPORT VEHICLES For Golf Course

Product information

2 Seats Utility Golf Cart	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28km/h
Range (loaded) based on flat road at a speed of 20km/h	28km/h
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgs
Dimensions	
Overall dimensions: LWH (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO/SOC, Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

2 Kişilik Golf Arabası

Z2 Beyaz

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkışı 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	28km/h
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	530kgsv
Boyutlar	
Genel boyutlar: LVH (mm)	2370*1210*1950mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlenebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş ışığı	
9inç dokunmatik ekran ile ters kamera fonksiyonu	Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



2 Person Golf Cart Z2 White

PASSENGER TRANSPORT VEHICLES

For Golf Course

Product information

2 Seats Utility Golf Cart	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgs
Dimensions	
Overall dimensions: L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Golf Sahası için

4 Kişilik Yardımcı Golf Arabası Z2C Beyaz

Ürün Bilgisi

2 Kişilik Yardımcı Golf Arabası	
Model	Z2
Sistem	48V 4KW AC sistem
Anahtar bileşenler	
Pil	Zhongyi Büyük kapasiteli derin döngülü kurşun asit pil 6*8V 140AH
Motor	4 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum dış kabuk, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	2
Maks. hız	28kmh
Menzil (yükli) şuna göre: 20km/s hızla düz yol	28kmh
Minimum dönüş yarıçapı	25m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	530kgsv
boyutlar	
Genel boyutları: LVH (mm)	2370*1210*1950mm
ön/arka tekerlek mesafesi (mm)	front 880mm/ rear 998mm
Dingil mesafesi (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Otomotiv mühendisliği malzemelerinin enjeksiyonla kalıplanması Ağırlık ve renk olarak hafif, solması kolay değil.
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli köpüklü süngerden yapılmış lüks koltuklar suni deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Plastik kalıp gösterge panosu elektrik anahtarı anahtarı, kilitlebilir Saklama kutusu, bardaklık, mobil tutucular, dönüş sinyali göstergesi, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2USB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Tempered glass with wiper Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stilli dönüş ışığı	
9inç dokunmatik ekran ile ters kamera fonksiyonu	Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dıkme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Caz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	On mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



4 Person Utility Golf Cart Z2C White

PASSENGER TRANSPORT VEHICLES

For Golf Course

Product information

2 Seats Utility Golf Cart	
Model	Z2
System	48V 4KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	4 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	2
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight(with batteries)	530kgs
Dimensions	
Overall dimensions: L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations(S for Standard, O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Yardımcı Golf Arabası Z4C Sarı

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor; yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükli) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LVH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektrofrezis pas önleyici çelik şasi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Utility Golf Cart PASSENGER TRANSPORT VEHICLES

Z4C Yellow

For Hotels

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions: LVH(mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Yardımcı Golf Arabası Z4C Yeşil

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükü) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektroforez pas önleyici çelik şasi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirilebilir
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Utility Golf Cart Z4C Green

PASSENGER TRANSPORT VEHICLES

For Hotels

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge. Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti-rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Golf Arabası Kargo Kutulu Z6B Beyaz

Ürün Bilgisi

6 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum shell, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj girişi voltajı 220V, çıkışı 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30km/h (ayarlanabilir)
Menzil (yükli) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	T740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektroforezi pas önleyici çelik şasi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirilebilir
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz fanı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Golf Cart with Cargo Box Z6B White

PASSENGER TRANSPORT VEHICLES

For Hotels

Product information

6 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shellSeal, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full chargeProtection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding modeling design separable replacement
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing , carbon fiber style, plastic molding instrument board electric key switch,lockable storage box, cup holder,professional combination meter with turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle,leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10





Sertemcar

YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Yardımcı Golf Arabası Z4C Beyaz

Ürün Bilgisi

6 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükli) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutları: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm / rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektrofrezis pas önleyici çelik şasi
Braket	Kalıp ağırla ile profesyonelce tasarlanmış ve kaynaklanmış yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar; Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Utility Golf Cart Z4C White

PASSENGER TRANSPORT VEHICLES For Hotels

Product information

6 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shellSeal, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full chargeProtection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding modeling design separable replacement
Support frame	the front steel,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing , carbon fiber style, plastic molding instrument board electric key switch,lockable storage box, cup holder,professional combination meter with turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle,leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



**SertemCAR**

YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Yardımcı Golf Arabası Z4C Simli

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum shell, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği, aracın sürüş mesafesini iyileştirmek için yokta güç, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükli) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: L*W*H (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektroforez pas önleyici çelik şasi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey puskurtulur, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirilebilir
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar, deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçek, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	iki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	iki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Güneş farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



www.sertemcar.com

6 Kişilik Yardımcı Golf Arabası Z4C Simli

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge. Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30km/h (adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight (with batteries)	770KG kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti-rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2x USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield (organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box (with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



Ürün Bilgisi

6 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum shell, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj girişi voltajı 220V, çıkışı 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30km/h (ayarlanabilir)
Menzil (yükü) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	70KG kgs
Dimensions	
Genel boyutları: L*W*H (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/ rear 998mm
ön/arka tekerlek mesafe (mm)	T740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Çözümler ve Çerçeve	
şasi	Asitleme fosfatlama elektroforez pas önleyici çelik şasi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Utility Golf Cart Z4C Silvery

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge. Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Carts weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions LWH (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations(S for Standard; O for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10





Sertemcar

YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Yardımcı Golf Arabası Z4C Kırmızı

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj girişi voltajı 220V, çıkışı 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükü) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutları: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	T740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektrofrez pas önleyici çelik şasi
Braket	Kalp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirilebilir
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam
	Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Utility Golf Cart Z4C Red

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10





SertemCAR

YOLCU TAŞIMA ARAÇLARI

Oteller için

6 Kişilik Kullanışlı Golf Arabası Z4C Siyah

Ürün Bilgisi

6 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokta güç, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruması işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükü) şuna göre: 20km/h hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektrofrez pas önleyici çelik şasi
Braket	Kalp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey puskurtulur, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabılır değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



www.sertemcar.com

PASSENGER TRANSPORT VEHICLES

For Hotels

6 Person Handy Golf Cart Z4C Black

Product information

6 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Oteller için

4 Kişilik Golf Arabası

Z4 Beyaz

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademesiz hız ayarı, tamamen kapalı alüminyum shellSeal, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj Koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükü) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LxVxH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektroforezi pas önleyici çelik şasi
Braket	Kalıp açma ile profesyonellerce tasarlanmış ve kaynaklanmış, yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



4 Person Golf Cart Z4 White

PASSENGER TRANSPORT VEHICLES For Hotels

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions LWH (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing, carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield (organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box (with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10





Sertemcar

YOLCU TAŞIMA ARAÇLARI

Oteller için

8 Kişilik Yardımcı Golf Arabası Z6C Beyaz

Ürün Bilgisi

8 Kişilik Yardımcı Golf Arabası	
Model	Z6C
Sistem	48V 5KW AC sistem
Anahtar bileşenler	
Pil	Torch marka kurşun asitli akü sulu 140 AH 8v 6 adet
Motor	Zhongyi Marka 5 KW Asenkron AC motor, yüksek verimlilik ve enerji tasarrufu, kademeli hız ayarı, tamamen kapalı alüminyum shell, iyi ısı dağılımı, yüksek çıkış verimliliği, güçlü aşırı yük/tırmanma yeteneği. Bakım gerektirmeyen.
Denetleyici	AC 48V 400A akıllı kontrolör, tırmanma yeteneği. Aracın sürüş mesafesini iyileştirmek için yokuşta güçlü, geri dönüş önleme, yokuş aşağı hız sınırı, frenleme veya ters enerji geri besleme kontrolü.
Şarj cihazı	Bilgisayar akıllı araç şarj cihazı, tam şarj süresi, tam şarj koruma işlevinden sonra otomatik kapanma koruması ile yaklaşık 6-8 saattir. Şarj giriş voltajı 220V, çıkış 48V/25A, koruma sınıfı: IP67.
Verim	
yolcu kapasitesi	6
Maks. hız	25-30kmh (ayarlanabilir)
Menzil (yükli) şuna göre: 20km/s hızla düz yol	70-90km
Minimum dönüş yarıçapı	6m
Maks. tırmanma yeteneği	20%
Mola Mesafesi	<6M
Arabanın ağırlığı (pillerle birlikte)	770KG kgs
Dimensions	
Genel boyutlar: LWH (mm)	4160*1210*1980mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme fosfatlama elektroforez pas önleyici çelik şasi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar, deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama. Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Ön çelik fırça koruması	
Emniyet kemerleri	İki noktalı kemer
ön cam	Katlanmış Ön Cam (organik cam)
9 inç ekran	Bluetooth radyo eğlence sistemi ve geri görüş kamerası ile
Buz kutusu (kutu tutuculu)	
Gövde örtüsü	
Yağmurluk	
Güneş Perdesi	Bir sepette 4 adet
Elektrik sistemi	
Aydınlatma sistemi	Tüm LED farlar: Lensli Ön Uzun/Kısa far; Ön ve arka Akan su dönüş sinyali ışığı; Gündüz farı
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



8 Person Utility Golf Cart Z6C White

Product information

8 Seats Utility Golf Cart	
Model	Z6C
System	48V 5KW AC system
Key Components	
Battery	Torch brand lead acid battery watered 140 AH 8v 6pcs
Motor	Zhongyi Brand 5 KW Asynchronous AC motor, high efficiency and energy saving, stepless speed regulation, fully enclosed aluminum shell, good heat dissipation, high output efficiency, strong overload/climbing ability. Maintenance free.
Controller	AC 48V 400A intelligent controller, climbing ability Strong, anti-rollback on the slope, speed limit on downhill, braking or reverse energy feedback control to improve the driving mileage of the vehicle
Charger	Computer intelligent car charger, full charge time is about 6-8 hours, with automatic power off protection after full charge. Protection function. Charge input voltage 220V, output 48V/25A, protection grade: IP67.
Performance	
Passenger capacity	6
Max. speed	25-30kmh(adjustable)
Range (loaded) based on flat road at a speed of 20km/h	70-90km
Minimum turning radius	6m
Max. climbing ability	20%
Break Distance	<6M
Cart's weight(with batteries)	770KG kgs
Dimensions	
Overall dimensions L*W*H (mm)	4160*1210*1980mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Pickling phosphating electrophoresis anti rust steel chassis
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding modeling design separable replacement
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Water transfer printing , carbon fiber style, plastic molding instrument board electric key switch, lockable storage box, cup holder, professional combination meter with turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2xUSB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Front steel brush guard	
Safety Belts	Two-point belt
Windshield	Folded Windshield(organic glass)
9 inch screen	With bluetooth radio entertainment system and reversing camera
Ice box(with box holder)	
Body cover	
Rain cover	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	All LED lights: Front High/Low beam with lens; Front and Rear Flowing water turn signal light; Daytime running light
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



**Sertemcar**

YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

6 Kişilik Gezi Arabası A6+ Beyaz

Ürün Bilgisi

6 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutları: LWH (mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/ rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemeri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stili dönüş işi	
9 inç dokunmatik ekran ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



6 Person Sightseeing Trolley A6+ White

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

6 Seats Utility Golf Cart	
Model	Z4C
System	48V 5KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	Zhongyi Brand 5KW AC motor
Controller	AC Controller (48V 400A)
Charger	On board Input 220V/110V, output 48V, 25A
Performance	
Passenger capacity	6
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	25m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight(with batteries)	530kgsv
Dimensions	
Overall dimensions: LWH(mm)	2370×1210×1950mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO/SOC, Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10





SertemCAR

YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

17 Kişilik Gezi Arabası A17 Yeşil

Ürün Bilgisi

17 Kişilik Elektrikli Gezi Otobüsü	
Model	A17+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutları: LWH (mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroferez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemeri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş işığı	
9 inç dokunmatik ekran ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



17 Person Sightseeing Trolley A17 Green

PASSENGER TRANSPORT VEHICLES


Scenic Spot

Product information

17 Seats Utility Golf Cart	
Model	Z4C
System	48V 5KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	Zhongyi Brand 5KW AC motor
Controller	AC Controller (48V 400A)
Charger	On board Input 220V/110V, output 48V, 25A
Performance	
Passenger capacity	6
Max. speed	28km/h
Range (loaded) based on flat road at a speed of 20km/h	28km/h
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight(with batteries)	530kgsv
Dimensions	
Overall dimensions: L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations('S' for Standard, 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension; Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



**SertemCAR**

YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

17 Kişilik Gezi Arabası A17 Beyaz

Ürün Bilgisi

17 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutlar: LxWxH (mm)	5980x1510x2135mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış,yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçek,hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçek KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stil dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



Ürün Bilgisi

14 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükü) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutlar: LWH (mm)	5980×1510×2135mm
ön/arka tekerlek mesafe (mm)	front:880mm/ rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçe, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstil dönüş ışığı	
9 inç dokunmatik ekran ters kamera fonksiyonu	le Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli (1.22m x 0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Caz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



14 Person Sightseeing Trolley A14 Blue

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

14 Seats Utility Golf Cart	
Model	Z4C
System	48V 5KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	Zhongyi Brand 5KW AC motor
Controller	AC Controller (48V 400A)
Charger	On board Input 220V/110V, output 48V, 25A
Performance	
Passenger capacity	6
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	25m
Max climbing ability	20%
Break Distance	<4M
Cart's weight(with batteries)	530kgsv
Dimensions	
Overall dimensions: LWH (mm)	2370×1210×1950mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	1740mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Braket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch,lockable storage box, cup holder,mobile holders,turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller,High accuracy speed meter KPH/MPH,ODO,SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie,and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle/leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

14 Kişilik Gezi Arabası A14 Yeşil

Ürün Bilgisi

14 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükü) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	25m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	510kgs
Dimensions	
Genel boyutları: LWH(mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçeği, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stili dönüş ışığı	
9 inç dokunmatik ekran ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Caz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



14 Person Sightseeing Trolley A14 Green

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

14 Seats Utility Golf Cart	
Model	Z4C
System	48V 5KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	Zhongyi Brand 5KW AC motor
Controller	AC Controller (48V 400A)
Charger	On board Input 220V/110V, output 48V, 25A
Performance	
Passenger capacity	6
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgsv
Dimensions	
Overall dimensions L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO/SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

14 Kişilik Gezi Arabası A14 Byaz

Ürün Bilgisi

14 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/ş hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	1310kgs
Dimensions	
Genel boyutlar: LWH (mm)	5980×1510×2135mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Çövede ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçek,hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçek KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stili dönüş ışığı	
9 inç dokunmatik ekranlı ters kamera fonksiyonu	9 inç dokunmatik ekranlı Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi, Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



14 Person Sightseeing Trolley A14 White

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

14 Seats Utility Golf Cart	
Model	Z4C
System	48V 5KW AC system
Key Components	
Battery	Zhongyi Huge capacity deep cycle lead-acid battery 6*8V 140AH
Motor	Zhongyi Brand 5KW AC motor
Controller	AC Controller (48V 400A)
Charger	On board Input 220V/110V, output 48V, 25A
Performance	
Passenger capacity	6
Max. speed	28kmh
Range (loaded) based on flat road at a speed of 20km/h	28kmh
Minimum turning radius	2.5m
Max. climbing ability	20%
Break Distance	<4M
Cart's weight (with batteries)	530kgsv
Dimensions	
Overall dimensions L*W*H (mm)	2370*1210*1950mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase (mm)	1740mm
Detailed Configurations (S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

11 Kişilik Gezi Arabası A11 Yeşil

Ürün Bilgisi

11Seater Electric Sightseeing Bus	
Model	A11
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions LWH (mm)	4380x1510x2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/ rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer, key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steeing is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcperson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Securitylight	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



11 Person Sightseeing Trolley A11 Green

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

11Seater Electric Sightseeing Bus	
Model	A11
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4380*1510*2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer,key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steering is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcpherson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Security light	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



**Sertemcar**

YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

11 Kişilik Gezi Arabası A11 Beyaz

Ürün Bilgisi

11 seater sightseeing cart A11 white	
Model	A11
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4380*1510*2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer,key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steeing is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcperson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Security light	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



www.sertemcar.com

11 Person Sightseeing Trolley A11 White

PASSENGER TRANSPORT VEHICLES Scenic Spot

Product information

11Seater Electric Sightseeing Bus	
Model	A11
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4380×1510×2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer,key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steeing is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcperson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Security light	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



**Sertemcar**

YOLCU TAŞIMA ARAÇLARI

Manzaralı Nokta

8 Kişilik Gezi Arabası A8 Yeşil

Ürün Bilgisi

8 Seater Electric Sightseeing Bus	
Model	A8
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions L*W*H (mm)	4380*1510*2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer,key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steeing is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcperson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Security light	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



www.sertemcar.com

8 Person Sightseeing Trolley A8 Green

PASSENGER TRANSPORT VEHICLES

Scenic Spot

Product information

8 Seater Electric Sightseeing Bus	
Model	A11
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	AC (400A)
Charger	On board 48V/30A
Performance	
Passenger capacity	11
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	3.8m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	980kgs
Dimensions	
Overall dimensions: L*W*H (mm)	4380*1510*2180mm
Min. ground clearance (mm)	150mm
Axle distance	2000mm
Wheelbase (mm)	front 1220mmmm/rear 1200mm
Body and Frame	
Frame	All aluminum frame
Body	Moulded injection plastic PP

Roof	Injection moulded modeling design separable replacement
Seats	Sponge&artificial Leather,adjustable driver's seat
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board with volt meter, ammeter, electricity indicator, speedometer,key switch, radio, USB plug, storage box, cup holder
Tires	Aluminum hub wheel 155R12C
EPS	Electric Power Steeing is equipped
Chassis	High strength structural steel
Steering	Gear steering+ auto backlash compensation
Braking System	Front disk +rear drum ,double circuit hydraulic brake+ hand brake
Front Axle	Mcperson independent suspension Spiral spring + cylinder hydraulic shock absorption
Rear Axle	Strengthen 16.7 Integral rear axle, Non independent suspension, leaf spring +cylinder hydraulic shock absorption
Detailed Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)	
Body And Frame	
Windshield	Laminated glass with wiper
Seats cover	
Safety Belts	
Security light	with loud speaker
Trailer Hook	
Body cover	
Sunshine Curtain	
rain cover	
Heater	
Fans	
Reviewer mirror outside	



YOLCU TAŞIMA ARAÇLARI

Soğuk Durum İçin

14 Kişilik Kapalı Gezi Arabası A14F Beyaz

Ürün Bilgisi

14 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	1310kgs
Dimensions	
Genel boyutlar: LWH (mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroferez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	iki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar ok stili dönüş işi	9 inç dokunmatik ekran ters kamera fonksiyonu
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	On mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



14 Person Closed Sightseeing Trolley A14F White



PASSENGER TRANSPORT VEHICLES For Cold Condition

Product information

14 seater enclosed sightseeing cart A14F white	
Model	A14F
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	USA brand Curtis 1232(400A)
Charger	On board 72V/30A
Performance	
Passenger capacity	14
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	5.4m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	1070kgs
Dimensions	
Overall dimensions: LWH (mm)	5180×1510×2125mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase (mm)	front 1240mmmm/ rear 1220mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield (organic glass)
Rain cover	
Ice box (with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel (1.22m x 0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



www.sertemcar.com

YOLCU TAŞIMA ARAÇLARI

Soğuk Durum İçin

11 Kişilik Kapalı Gezi Arabası

A11F Beyaz

Ürün Bilgisi

11 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	1310kgs
Dimensions	
Genel boyutları: LWH (mm)	5980×1510×2135mm
ön/arka tekerlek mesafe (mm)	front:880mm/rear:998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Çövede ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey puskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Çövede ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabılır değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer,hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



11 Person Closed Sightseeing Trolley A11F White



PASSENGER TRANSPORT VEHICLES For Cold Condition

Product information

11 seater enclosed sightseeing cart A11F white	
Model	A11F
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	USA brand Curtis 1232(400A)
Charger	On board 72V/30A
Performance	
Passenger capacity	14
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	5.4m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	1070kgs
Dimensions	
Overall dimensions: L*W*H (mm)	5180*1510*2125mm
front/rear wheel distance (mm)	front:880mm/rear:998mm
Wheelbase(mm)	front:1240mmmm/rear:1220mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brakes system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



www.sertemcar.com

YOLCU TAŞIMA ARAÇLARI

Soğuk Durum İçin

8 Kişilik Kapalı Gezi Arabası A8F Beyaz

Ürün Bilgisi

14 Kişilik Elektrikli Gezi Otobüsü	
Model	A6+
Sistem	72V /7.5KW AC system
Anahtar bileşenler	
Pil	Huge capacity deep cycle lead-acid battery 6V/piece 12 pieces,230Ah
Motor	7.5KW AC motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	1310kgs
Dimensions	
Genel boyutlar: LxWxH (mm)	5980x1510x2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/ rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçek, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	iki noktali kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçek KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli (1.22m x 0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



8 Person Closed Sightseeing Trolley A8F White



PASSENGER TRANSPORT VEHICLES

For Cold Condition

Product information

8 Seater Electric Sightseeing Bus	
Model	A8F
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	USA brand Curtis 1232(400A)
Charger	On board 72V/30A
Performance	
Passenger capacity	14
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	5.4m
Max. climbing ability	15%
Break Distance	<4M
Carts weight(with batteries)	1070kgs
Dimensions	
Overall dimensions: L*W*H (mm)	5180*1510*2125mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	front 1240mmmm/ rear 1220mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body & Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch,lockable storage box, cup holder,mobile holders,turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller,High accuracy speed meter KPH/MPH,ODO,SOC.Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie,and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle,leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



www.sertemcar.com

YOLCU TAŞIMA ARAÇLARI

Lüks Yer İçin

8 Kişilik Eski Model Araba Y8 Kırmızı ve Sarı

Ürün Bilgisi

8 Kişilik Elektrikli Gezi Otobüsü	
Model	GD8-Y8
Sistem	48V /5KW AC system
Anahtar bileşenler	
Pil	Ücretsiz bakım aküsü 8*6V 200AH
Motor	5 KW Motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutlar: LWH (mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S', Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp ağma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey puskurtulmuş, şekli bastır, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirilebilir
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar, deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölcer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölcer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş göğü	
9 inç dokunmatik ekran ters kamera fonksiyonu	9 inç dokunmatik ekran ters kamera fonksiyonu
Güneş paneli	Tek parça 200W Güneş Paneli (1.22m x 0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Caz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



8 Person Vintage Car Y8 Red and Yellow

PASSENGER TRANSPORT VEHICLES

For Luxury Place

Product information

8 Seats Classic Car	
Model	GD8-Y8
System	48V /5KW AC system
Key Components	
Battery	free maintenance battery 8*6V 200AH
Motor	5 KW Motor
Controller	Enpower Controller 400A
Charger	portable charger
Performance	
Passenger capacity	8
Max. speed	28km/h
Range (loaded) based on flat road at a speed of 20km/h	80-90 km
Minimum turning radius	7m
Max climbing ability	0.15
Break Distance	<4.5M
Cartsweight(with batteries)	963 kgs
Dimensions	
Overall dimensions L*W*H (mm)	5180*1510*2125mm
front/rear wheel distance (mm)	front 880mm/ rear 998mm
Wheelbase(mm)	front 1240mmmm/ rear 1220mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Braket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch,lockable storage box, cup holder,mobile holders,turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
	Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller,High accuracy speed meter KPH/MPH,ODO,SOC. Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie,and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle/leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



YOLCU TAŞIMA ARAÇLARI

Lüks Yer İçin

4 Kişilik Eski Model Araba Y4 Beyaz ve Mavi

Ürün Bilgisi

4 Kişilik Klasik Araba	
Model	GD4-Y4
sistem	48V /5KW AC sistemi
Anahtar bileşenler	
Pil	ücretsiz bakım aküsü 6*8V 150AH
Motor	5 KW Motor
Denetleyici	Güç Denetleyicisi 400A
Charger	taşınabilir şarj cihazı
Verim	
yolcu kapasitesi	4
Maks. hız	28km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	80-100 km
Minimum dönüş yarıçapı	4m
Maks. tırmanma yeteneği	0.15
Mola Mesafesi	<4.5M
Arabanın ağırlığı (pillerle birlikte)	744 kgs
boyutlar	
Genel boyutlar: L*W*H (mm) ön/arka tekerlek mesafe (mm)	3330*1640*1990mm front 1145mm/rear 1150mm
Dingil mesafesi (mm)	1905mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Kaynaklı yüksek akma mukavemetli alüminyum malzeme
Braket	Kalip açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Yüksek mukavemetli kompozit gövde
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Premium deri koltuk
Gösterge Paneli	"Maun" gösterge tablosu, ampermetre ile lüks araba içi, kombinasyon aleti, kontak anahtarı, elektrik göstergesi, CD makinesi, ileri ve geri anahtarı
Emniyet kemerleri	Two-point belt
ön cam	Silecekli temperli cam
Yağmurluk	
Gövde örtüsü	
Güneş Perdesi	bütün sepet
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistem	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	ön hidrolik disk fren ve arka hidrolik kampanalı fren
Accelerator	Gaz pedalı
Süspansiyon sistemi	ön : Bükümlü yapı arka : plaka Yay + Silindirik Hidrolik Amortisör
tekerlek ve Lastik	wheel & Tyre



4 Person Vintage Car Y4 White and Blue

PASSENGER TRANSPORT VEHICLES

For Luxury Place

Product information

4 Seats Classic Car	
Model	GD4-Y4
System	48V /5KW AC system
Key Components	
Battery	free maintenance battery 6*8V 150AH
Motor	5 KW Motor
Controller	Enpower Controller 400A
Charger	portable charger
Performance	
Passenger capacity	4
Max. speed	28km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	4m
Max. climbing ability	0.15
Break Distance	<4.5M
Cart's weight(with batteries)	744 kgs
Dimensions	
Overall dimensions: L*W*H (mm)	3330*1640*1990mm
front/rear wheel distance (mm)	front1145mm/rear1150mm
Wheelbase(mm)	1905mm
Detailed Configurations('S' for Standard; 'O' for Option)	
Body and Frame	
Chassis	Welded high yield strength aluminium material
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	High strength composite body
Support frame	the front steel ,the rear aluminum
Seats	Premium leather seat
Dashboard	Luxury car interior with "mahogany" instrument table, ammeter, combination instrument, ignition switch, electricity indicator, CD machine, forward and backward switch
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper
Rain cover	
Body cover	
Sunshine Curtain	whole cart
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	front hydraulic disc brake and rear hydraulic drum brake
Accelerator	electric accelerator
Suspension system	front :Twister structure rear :plate Spring + Cylindrical Hydraulic Shock Absorb
wheel & Tyre	wheel & Tyre





SertemCAR

YOLCU TAŞIMA ARAÇLARI

Mini Kamyon

0.5 Tonluk Elektrikli Kamyon

Ürün Bilgisi

8 Kişilik Elektrikli Gezi Otobüsü	
Model	GD8-Y8
Sistem	48V /5KW AC system
Anahtar bileşenler	
Pil	ücretsiz bakım aküsü 8*6V 200AH
Motor	5 KW Motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükü) suna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	310kgs
Dimensions	
Genel boyutları: L*W*H (mm)	5980*1510*2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/ rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için 'S'; Seçenek için 'O')	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akıma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış, yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabılır değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar, deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçek, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçek KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş işiği	
9 inç dokunmatik ekran ters kamera fonksiyonu	16 Radyo, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli (1.22m x 0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedalı	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



PASSENGER TRANSPORT VEHICLES

Mini Truck

O.5 Ton Electric Truck

Product information

11 seater enclosed sightseeing cart A11F white	
Model	A11F
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	USA brand Curtis 1232(400A)
Charger	On board 72V/30A
Performance	
Passenger capacity	14
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	5.4m
Max. climbing ability	15%
Break Distance	<4M
Cart's weight(with batteries)	1070kgs
Dimensions	
Overall dimensions: L*W*H (mm)	5180*1510*2125mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	front 1240mmmm/rear 1220mm
Detailed Configurations(S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel, the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch, lockable storage box, cup holder, mobile holders, turn signal indicator, speed indicator and mileage, forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller, High accuracy speed meter KPH/MPH, ODO, SOC, Multi-page display with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie, and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle, leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10



**Sertemcar**

YOLCU TAŞIMA ARAÇLARI

Temizlik İçin

0.5 Tonluk Kargo Kutulu Elektrikli Kamyon

Ürün Bilgisi

8 Kişilik Elektrikli Gezi Otobüsü	
Model	GDB-Y8
Sistem	48V /5KW AC system
Anahtar bileşenler	
Pil	ücretsiz bakım aküsü 8*6V 200AH
Motor	5 KW Motor
Denetleyici	AC 7.5kw 400A
Şarj cihazı	On board 72V/30A
Verim	
yolcu kapasitesi	17
Maks. hız	30km/h
Menzil (yükli) şuna göre: 20km/s hızla düz yol	110-120 km
Minimum dönüş yarıçapı	2.5m
Maks. tırmanma yeteneği	15%
Mola Mesafesi	<4M
Arabanın ağırlığı (pillerle birlikte)	1310kgs
Dimensions	
Genel boyutları: LWH (mm)	5980×1510×2135mm
ön/arka tekerlek mesafe (mm)	front 880mm/rear 998mm
ön/arka tekerlek mesafe (mm)	1740mm
Ayrıntılı Konfigürasyonlar (Standart için S; Seçenek için O)	
Gövde ve Çerçeve	
şasi	Asitleme ve fosfatlama ile kaynaklı yüksek akma dayanımlı boru çeliği elektroforez işlemi
Braket	Kalıp açma ile profesyonelce tasarlanmış ve kaynaklanmış yüzey püskürtülür, şekli basittir, kalitesi yüksektir ve paslanmaya karşı dayanıklıdır.

Gövde ve Çatı	Enjeksiyon kalıplama modelleme tasarımı ayrılabilir değiştirme
destek çerçevesi	ön çelik, arka alüminyum
Koltuklar	Yüksek kaliteli taklit köpüklü süngerden yapılmış lüks koltuklar deri koltuk, yüksek esneklik ve kolay deforme olmaz.
Gösterge Paneli	Su transfer baskı, karbon fiber stili, plastik kalıplama Enstrüman panosu elektrik anahtarı anahtarı, kilitlenebilir saklama kutusu, fincantutucu, dönüş sinyali göstergeli profesyonel kombinasyon ölçer, hız göstergesi ve kilometre, ileri ve Revize göstergesi. 2xUSB şarj bağlantı noktası.
Emniyet kemerleri	İki noktalı kemer
ön cam	Silecekli temperli cam Katlanmış Ön Cam (organik cam)
Yağmurluk	
Buz kutusu (kutu tutuculu)	
Golf topu yıkayıcı	
kum şişesi	
Caddy beklemede	
Sunshine Curtain	Güneş Perdesi
Elektrik sistemi	
Aydınlatma sistemi	Otomotiv seviyesi aydınlatma kombinasyonu tasarımı, üst düzey, gündüz farları dahil uzun ömürlü LED farlar, melek gözlü uzun/kısa farlar, sürüş/fren arka lambaları, ve ön/arka akan su dönüş lambaları.
Yuvarlak LCD dijital enstrüman	Denetleyiciye CAN iletişimi, Yüksek doğruluklu hız ölçer KPH/MPH, ODO, SOC. Denetleyici teşhis bilgileri ile çok sayfalı ekran.
yan aynalar okstili dönüş ışığı	
9 inç dokunmatik ekran ile ters kamera fonksiyonu	Radio, Müzik, Film ve ters görüntü kamerası
Güneş paneli	Tek parça 200W Güneş Paneli(1.22m x0.92m)
Direksiyon ve Süspansiyon Sistemi	
Direksiyon sistemi	Çift otomotiv tarzı dikme ve kendinden ayarlı kremayer ve pinyon direksiyon
Fren sistemi	Çift arka tekerlek mekanik kampanalı frenler, kendinden ayarlı asbest olmayan astarlar
Gaz pedali	elektrikli hızlandırıcı
Süspansiyon sistemi	Ön mcpherson bağımsız süspansiyon, Spiral yay + silindir hidrolik şok emilimi; Entegre arka aks, yaprak yay + silindir hidrolik şok emilimi
tekerlek ve Lastik	Alüminyum poyra 205/50-10



**Sertemcar**

O.5 Tonluk Kargo Kutulu PASSENGER TRANSPORT VEHICLES

Elektrikli Kamyon

For Cleaning

Product information

11 seater enclosed sightseeing cart A11F white	
Model	A11F
System	48V /5KW AC system
Key Components	
Battery	Huge capacity deep cycle lead-acid battery 6V/piece 8 pieces,210Ah
Motor	5KW AC motor
Controller	USA brand Curtis 1232(400A)
Charger	On board 72V/30A
Performance	
Passenger capacity	14
Max. speed	30km/h
Range (loaded) based on flat road at a speed of 20km/h	80-100 km
Minimum turning radius	5.4m
Max. climbing ability	15%
Break Distance	<4M
Carts weight(with batteries)	1070kgs
Dimensions	
Overall dimensions LWH(mm)	5180×1510×2125mm
front/rear wheel distance (mm)	front 880mm/rear 998mm
Wheelbase(mm)	front 1240mmmm/rear 1220mm
Detailed Configurations(S for Standard; O for Option)	
Body and Frame	
Chassis	Welded high yield strength tubular steel with pickling and phosphating electrophoresis process
Bracket	Professionally designed and welded by mold opening, the surface is sprayed, the shape is simple, the quality is high, and it is anti-rust.

Body &Roof	Injection molding of automotive engineering materials is light in weight and color not easy to fade.
Support frame	the front steel ,the rear aluminum
Seats	Luxurious seats made of foamed sponge high-grade imitation leather seat, high resilience and not easy to deform.
Dashboard	Plastic molding instrument board electric key switch,lockable storage box, cup holder,mobile holders,turn signal indicator, speed indicator and mileage,forward and Reverse indicator. 2USB charger port.
Safety Belts	Two-point belt
Windshield	Tempered glass with wiper Folded Windshield(organic glass)
Rain cover	
Ice box(with box holder)	
Golf ball washer	
Sand bottle	
Caddy standy	
Sunshine Curtain	4 pcs in a whole cart
Electric System	
Lighting system	Automotive level lighting combination design, high-end, long-lasting LED lights, including daytime driving lights, high/low beam with angel eyes head lights, drive/break tail lights, and front/rear flowing water turning lights.
Round LCD digital instrument	CAN communication to the controller,High accuracy speed meter KPH/MPH,ODO,SOC. Multi-page display,with controller diagnostic information.
Side mirrors with arrow style turning light	
9 inch touch screen with reverse camera function	Radio, Music, Movie,and reverse image camera
Solar Panel	One piece 200W Solar Panel(1.22m x0.92m)
Steering and Suspension System	
Steering system	Dual automotive-style strut and self-adjust rack-and pinion steering
Brake system	Dual rear wheel mechanical drum brakes ,self-adjusting with non-asbestos linings
Accelerator	electric accelerator
Suspension system	Front mcpherson independent suspension, Spiral spring + cylinder hydraulic shock absorption ; Integral rear axle,leaf spring + cylinder hydraulic shock absorption
wheel & Tyre	Aluminum hub 205/50-10


www.sertemcar.com